

4-Port AC1750 Wireless Gigabit Gateway with VoIP

NC-WR764TGV



Features

- Supports 802.11ac, Compatible with 802.11 b/g/n/ac products.
- Dual band – for combined wireless speeds of up to 1750bps at 2.4GHz and 5GHz band concurrently.
- USB3.0 Ports - easily share a printer locally and files & media with networked devices or remotely via FTP server.
- Easy one-touch wireless security encryption with the WPS button.
- Cost-Effective VoIP – Supports up to eight VoIP accounts and numerous call features, keeping phone costs low.
- Easy Setup Assistant provides quick & hassle free installation.

Description

The WR764TGV upgrades your network to the next generation of Wi-Fi. With combined wireless speeds of up to 1750Mbps, the device provides better speeds and wireless range. And it provides cost-effective VoIP services with 2 FXS Port. You can run multiple bandwidth intensive applications in a large home or office. Simple tasks like web browsing can be handled by the 2.4GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5GHz band at the same time. If you prefer a wired connection, WR764TGV has gigabit ports to provide a lightning-fast and lag-free experience. The USB3.0 ports will allow you to power a robust home Internet network by sharing printers, flash storage, ftp servers, or media players.

Specifications

General	
Wireless Standards	IEEE802.11 a/n/ac, 5GHz IEEE802.11 b/g/n, 2.4GHz
Signal Rate	5GHz: up to 1,300Mbps 2.4GHz: up to 450Mbps
Operation Frequency	2.4GHz and 5GHz
Receive Sensitivity	5GHz 11a 6Mbps: -96dBm, 11a 54Mbps: -79dBm 11ac HT20: -71dBm, 11ac HT40: -66dBm, 11ac HT80: -63dBm, 11n HT20: -72dBm, 11n HT40: -71dBm 2.4GHz 11g 54M: -77dBm 11n HT20: -74dBm, 11n HT40: -72dBm
Wireless Security	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption
VoIP Standards	SIP (RFC3261), ITU-T G.729/G.722/G.711a/G.711
Hardware	
Interfaces	1x 10/100/1000Mbps WAN Port 4x 10/100/1000Mbps LAN Port 2x FXS Port 1x USB 3.0 Port
Buttons	1x 10/100/1000Mbps WAN Port 4x 10/100/1000Mbps LAN Port 2x FXS Port 1x USB 3.0 Port
Power Supply	DC 12V 1A
Antenna	3x 5dBi dual band fixed antennas
Dimensions (W x D x H)	210 x 150 x 32 mm
Software Features	
WAN Type	Dynamic IP/Static IP/PPPoE
DHCP	Server, Client, DHCP Client List, Address Reservation
Quality of Service	WMM, Bandwidth Control
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
VPN Pass-Through	PPTP, L2TP, IPSec
Access Control	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security	DoS, SPI Firewall IP Address Filter / MAC Address Filter / Domain Filter IP and MAC Address Binding

Specifications

Software Features	
USB Sharing	Support Samba (Storage) / FTP Server / Media Server / Printer Server / DLNA
VoIP Features	Two RJ-11 FXS ports for connecting to analog telephones Call forwarding, call waiting, call block, 3-way conference call, etc.
Management	Access Control Local Management Remote Management
Internet Protocol	IPv4, IPv6
Environment	
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-40°C - 70°C (-40°F - 158°F)
Relative Humidity	10% - 90% non-condensing
Storage Humidity	5% - 95% non-condensing
Certifications	CE, RoHS
Package Contents	
Package Contents	1x Wireless Router 1x Power Adapter 1x Ethernet Cable 1x Quick Installation Guide